

SPECIFICATIONS

ASTM F 2413-05 Rated Titanium/Aluminum Lightweight,
Anti-Magnetic, Non-Sparking Safety Toe
*lightweight foot protection, low thermal conductivity

Leather and Nylon Upper
*durable and breathable, uniform code, polishable

Compression Molded EVA Midsole
*comfort, support

Slip-Resistant, Oil-Resistant Outsole
*safety and performance

YKK® Zipper with Velcro® Closure
*easy on and off

Removable Molded Orthotic Footbed
*allows for custom fit

Tough & Durable Moisture Wicking Lining
*durability, comfort, wicks moisture away from feet

Steel Shank
*torsional support

"Hot Melt" Heel Counter
*retains boot's shape, holds foot in place

Rust-Proof Hardware
*durability

Non-Fray Laces
*durability and strength



Style #	Size Range	Weight
1160	Regular Width (D) 5 - 11.5, 12, 13, 14, 15 EU (D) 36.5 - 45, 46, 47, 48.5, 50	55 oz. (1559) gm/pr Size 9 / 42
1160W	Wide Width (EEE) 8 - 11.5, 12, 13, 14, 15 EU (EEE) 40.5 - 45, 46, 47, 48.5, 50	55 oz. (1559) gm/pr Size 9 / 42



Classic 9" Light Safety Toe Side Zip

1160 · 1160W

29